

# PCIe-NX154PoE

100 TOPS Intelligent Frame Grabber Card with 4x PoE+ ports for IVA or AI Inspection



CE FC

## Key Features

- Powered by NVIDIA® Jetson Orin™ NX bundled with JetPack 5.1
- Single-slot half-length PCIe card form factor
- 4x PoE+ 2.5 GbE ports with a 50W total power budget
- 100 TOPS AI inference performance capable of up to four simultaneous streams of 4K@30FPS video decoding
- 1x isolated RS-485 and 1x RS-232
- x1 Gen2 PCI Express interface offering 2.5Gb/s total bandwidth
- -25°C to 60°C operating temperature with airflow

Contact Neosys

Get Quote

## Introduction

PCIe-NX154PoE is an intelligent 4-port 2.5GbE PoE+ frame grabber card fueling 100 TOPS AI inference performance for modern vision inspection, intelligent video analytics and surveillance/ security applications. Powered by NVIDIA's Jetson Orin NX system-on-module, PCIe-NX154PoE delivers 100 INT8 TOPS AI performance via its 1024 CUDA cores, 32 Tensor cores and 2 NVDLA® engines. It also features four 2.5GbE PoE+ ports with a 50W total PoE power budget to connect and power industrial GigE cameras or IP cameras.

With a standard single-slot half-length PCIe card form factor and utilizing 2.5GbE for host communication, PCIe-NX154PoE can be installed into a single PCIe x4 slot while operate on Gen2 x1 signals. This makes it an easy integration into any existing computer system, such as a 19" rack-mount IPC or commercial off-the-shelf box PC. When installed into a vision computer system, PCIe-NX154PoE provides necessary camera connectivity, and it also offloads the deep-learning image processing from host CPU/GPU since image capture, video streaming, pre-processing, and inference are all computed on PCIe-NX154PoE.

Wide temperature -25°C to 60°C operation capability, and compatibility with Windows and Linux operating systems make PCIe-NX154PoE the perfect upgrade for legacy machine vision systems to leverage deep learning-based image processing such as object detection, classification, tracking, facial recognition, etc. It's a revolutionary frame grabber card with intelligence for next-generation computer vision applications.

## Specifications

### System Core

Processor	Supporting NVIDIA® Jetson Orin™ NX system-on-module (SOM), comprising NVIDIA® Ampere GPU and ARM Cortex CPU
Memory	8GB/ 16GB LPDDR5 @ 3200 MHz on SOM

### Storage Interface

M.2 NVMe	1x M.2 2242 M key socket (PCIe Gen4 x2) for NVMe SSD
----------	------------------------------------------------------

### Deployment I/O Interface

Bus Interface	x1, Gen2 PCI Express
PoE	4x IEEE 802.3at PoE+. Max 25.5W per port. Total 50W power budget for 4 ports
Ethernet	4x 2.5GBASE-T Ethernet ports
Serial Port	1x RS-232 port and 1x isolated RS-485 port

### Development I/O Interface

Ethernet port	1x Gigabit Ethernet
USB	2x USB 2.0 ports 1x micro USB (OTG)
Video Port	1x DisplayPort, supporting 3840x2160 at 60Hz
DC Input	12V DC power input (for standalone development, or when total power consumption is more than 66W)

### Mechanical

Dimension	167.7 mm (W) x 111 mm (H)
Weight	TBD

### Environmental

Operating Temperature	-25°C to 60°C with airflow (20W TDP mode) *
Storage Temperature	-40°C ~85°C
Humidity	10%~90%, non-condensing
EMC	CE Class A, according to EN 55032/55035 (pending) FCC Class A, according to FCC Part 15, Subpart B (pending)

\* For sub-zero and over 60°C operating temperature, a wide temperature NVMe is required.

## Ordering Information

<i>Model No.</i>	<i>Product Description</i>
<i>PCIe-NX154-JON8</i>	100 TOPS Intelligent Frame Grabber with 4x PoE+ GbE ports by Jetson Orin NX (8GB)
<i>PCIe-NX154-JON16</i>	100 TOPS Intelligent Frame Grabber with 4x PoE+ GbE ports by Jetson Orin NX (16GB)

## Ordering Information

<i>PA-60W-OW</i>	60W AC/ DC power adapter 12V/ 5A; cord end terminals for terminal block, operating temperature: -30 to 60°C
------------------	-------------------------------------------------------------------------------------------------------------