

FPC-5210-P6

Distribué par :



Intel® 14th / 13th / 12th Gen. Core™ Embedded GPU Computer Supporting NVIDIA® RTX A4500 w/ 6x POEs



Features

- SMART FAN support
- 14th/13th/12th Gen Core™ i9/i7/i5/i3 Processor (Raptor Lake-Refresh/ Raptor Lake-S/Alder Lake-S)
- Up to 120W GPU MXM module expansion
- 6 x 802.3af (15.4W) Gigabit PoE ports
- Wide range DC power input (9~36V)
- DP x2 + HDMI x 1 and DVI x 1 (support 4 independent displays)
- Power on/off delay control / configurable ignition power control
- Supports TPM 2.0 and Time-Sensitive Networking (TSN)
- Two-mPCIe for optional WiFi/3G/4G/GPS or I/O expansion supported
- 1 x M.2 B-Key for storage or 5G / LTE +1 x M.2 E-Key for WiFi / BT
- 1 x M.2 M-Key for NVMe SSD

System

CPU	Intel® 14 th /13 th /12 th generation Core™ i9/i7/i5/i3 processor in LGA1700 socket (Max 65W CPU)
Memory	2 x 262-pin DDR5 SO-DIMM sockets, supporting 4800 MHz SDRAM up to 64GB (ECC/ Non-ECC)
Chipset	Intel® R680E
Graphics	Integrated Intel® HD Graphics 770
ATA	2 x Serial ATA ports with 600MB/s HDD transfer rate
LAN Chipset	1 x Intel® I219LM GbE controller w/ iAMT 16.0 3 x Intel® I226 2.5G GbE controllers 6 x Intel® I210 GbE controllers for PoE
Watchdog Timer	1~255 levels reset
TPM	Onboard TPM 2.0

I/O

Serial Port	2 x RS-232/422/485 configurable ports via DB-9 connectors (Default RS-232, Switch via BIOS)
USB Port	8 x USB 3.2 Gen2(10Gbps) /2.0 ports
LAN	4 x RJ-45 connectors for GbE 6 x RJ-45 connectors by Intel® I210(1GbE) max 60W supports 802.3af PoE 2 x DP 1.4a from MXM module or Intel Graphics (Default Intel Graphics switch via BIOS)
Display	1 x HDMI 2.0b female connector 1 x DVI-I female connector for digital / analog video output * Support 4 independent displays
DIO Port	1 x DB15 connector for 8 x digital input (Dry/ Wet contact) with 2KV isolation 1 x DB15 connector for 8 x digital output with 2KV isolation
Audio	Mic-in/Line-out
Expansion Bus	1 x MXM3.1 TYPE A/B GPU Slot (PCIe Gen5 x16) MXM A4500 Support 2 x mini-PCI Express Slots interconnected with SIM card sockets for optional WiFi/BT/3G/LTE/ GPS (PCIex1+USB2.0, Full Size) 3 x SIM sockets (2 for mPCIe / 1 for M.2 B key) 1 x M.2 B key (2242/3052/2280) w/ (PCIex2+USB3.0+SATA) interconnected with SIM for 5G / LTE or for storage (either one) 1 x M.2 E key (2230) with PCIe1+USB2.0+CNVi) for Wireless

Environmental

Operating Temp.	-20 ~ 55°C (-4 ~ 131°F), ambient w/ air flow (w/ 65W TDP CPU, 115W GPU)
Storage Temp.	-40 ~ 85°C (-40 ~ 185°F)
Operating Humidity	10 ~ 95% @ 55°C (non-condensing)
Vibration	5~500Hz 2G rms X,Y,Z axis w/SSD, according to IEC 60068-2-64
Shock	30 Grms, Half-sine 11 m sec. duration w/ SSD, according IEC60068-2-27

Qualification

Certification	CE, FCC Class A
---------------	-----------------

Power Requirement

Power Input	DC 9~36V input (w/ 4-pin DC input terminal block) (V+, V+, V-, V-)
Ignition Switch	2-pin terminal block: IGN, GND
Power Consumption	Max. 280W

Storage

Type	2 x 2.5" outside accessible drive bays 1 x M.2 B key (2242/2280) w/ (PCIex2+USB+SATA) for storage or LTE expansion (either one) 1 x M.2 2280 M key supports 2242, 2280 devices (PCIe x4 & SATA signal, support boot up function)
------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Mechanical

Construction	Metal
Mounting	Wall-mount
Weight	4.68 Kg (10.32lb)
Dimensions (W x D x H)	285 x 230 x 110mm (11.2" x 9.05" x 4.33")

OS Support

Windows 10 IOT Enterprise 64-bit
Linux (Ubuntu 20.04)


Ordering Information

FPC-5210-P6	Embedded GPU Computer, Bare Bone, w/6x POEs
-------------	---------------------------------------------

All specifications are subject to change without notice.

Distribué par Antéor - www.anteor.com - Tél.: 01 61 37 07 00

Dimensions



Standard Accessories

CPF-92Q0-C1

CPU Cooling for LGA1700 CPU



Optional Accessories

WMK-5210

Wall-mount kit for FPC-521x Series



PAC-360W7C-MW

360W AC/DC adapter kit w/ 4-pin terminal block



Optional Configuration (CTOS* Kit)

MXM-A4500-8G

MXM 3.1 Type B NVIDIA® Quadro® Embedded A4500-8GB-115W GDDR6 MXM GPU



MXM-A4500-16G

MXM 3.1 Type B NVIDIA® Quadro® Embedded A4500-16GB-115W GDDR6 MXM GPU

FAN-5210-GPU-A4500

GPU cooling for MXM-4500-GPU

MM-5C-8G/16G/32G

DDR5-4800 8GB/16GB/32G SDRAM DIMM module



WIFI-IN2550

Intel AX200NGW M.2 Wi-Fi 6 module w/2x30cm internal wires



ANT-H11

1 x 2dBi HSUPA antenna



ANT-D11

1 x WiFi dual-band 2.4G/5G antenna

Core™ i9-14900T

Intel® 14th Gen. Core™ i9-14900T processor, L3/36M, 1.1G

Core™ i7-14700T

Intel® 14th Gen. Core™ i7-14700T processor, L3/33M, 1.3G

Core™ i5-14500T

Intel® 14th Gen. Core™ i5-14500T processor, L3/24M, 1.7G

Core™ i3-14100T

Intel® 14th Gen. Core™ i3-14100T processor, L3/12M, 2.7G

Core™ i9-14900

Intel® 14th Gen. Core™ i9-14900 processor, L3/36M, 2.0G

Core™ i7-14700

Intel® 14th Gen. Core™ i7-14700 processor, L3/33M, 2.1G

Core™ i5-14500

Intel® 14th Gen. Core™ i5-14500 processor, L3/24M, 2.5G

Core™ i3-14100

Intel® 14th Gen. Core™ i3-14100 processor, L3/12M, 3.5G



*CTOS means Configure-to-Order Service.