



NC9KSL-2500 / NC9KDL-2550

1. INTEL® Cedar Trail-D Processor D2500 / D2550 + NM10 Chipset
2. Support 2 * DDR3 800/1067MHz
Single CH up to 4GB
3. Support 2 * Serial ATAll (3Gb/s) Devices
4. Integrated Realtek ALC662 HD Audio CODEC with 6-CH
5. 1 * 24 bits Single Channel LVDS header
6. Supports 2 * Realtek RT8111EVL Gigabit LAN
7. Support Watch dog Technology
8. Compliance with ErP standard
9. Mini-ITX Form Factor (170mm x 170mm)



Board Specifications

■ CPU	■ INTEL® Cedar Trail-D Processor D2500 (1.6GHz) / D2550 (1.86GHz)
■ Chipset	■ INTEL® NM10 Express chipset
■ Memory	■ 2 * DDR3 1067MHz Single CH SO-DIMM up to 4GB
■ Expansion Slots	■ 1 * PCI slot ■ Support Jetway Daughter Board
■ Storage	■ 2 * Serial ATA2 3Gb/s connectors
■ Audio	■ Realtek ALC662 6-Channel HD Audio
■ Ethernet LAN	■ 2 * RTL8111EVL PCI-E Gigabit LAN
■ LVDS	■ Onboard 24-bits single channel connector
■ USB	■ Embedded 8 * USB 2.0/1.1
■ Special Features	<ul style="list-style-type: none"> ■ Support ACPI S3 ■ Support CPU Smart FAN ■ Support Watch Dog
■ Rear Panel I/O	<ul style="list-style-type: none"> ■ 4 * USB 2.0/1.1 ports ■ 1 * PS/2 Mouse & 1 * Keyboard connector ■ 2 * RJ-45 port ■ 3 * Audio I/O ports (Line-in, MIC and Line-out) ■ 1 * VGA port ■ 1 * HDMI port
■ Internal I/O	<ul style="list-style-type: none"> ■ 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports ■ 2 * NB / Chassis Fan connectors; ■ 1 * 24-pin ATX Power connector ■ 1 * LVDS header/1 * Inverter header ■ 1 * AUDIO header ■ 1 * RS232 header ■ 1 * Parallel header
■ BIOS	■ AMI 16MB DIP Flash ROM
■ Form Factor	■ Mini ITX Form Factor(17cmx17cm)