



NF9D-2700 / NF9D-2550



Antéor

1. INTEL® Cedar Trail-D Processor D2700 / 2550 + NM10 Chipset
2. Support 2 * DDR3 800/1067MHz Single CH up to 4GB
3. Support 2 * Serial ATAI (3Gb/s) & 2 * Serial ATAIII (6Gb/s) Devices
4. Integrated Realtek ALC662 HD Audio CODEC with 6-CH
5. Supports 2 * Realtek RT8111EVL Gigabit LAN
6. 1 * 24 bits Dual Channel LVDS header
7. Support Watch dog Technology
8. Compliance with ERP standard
9. Mini-ITX Form Factor(170mm x 170mm)
10. Support Daughter board Expansion

Board Specifications

■ CPU	■ INTEL® Cedar Trail-D Processor D2700 CPU (2.13GHz) D2550 CPU(1.86GHz)
■ Chipset	■ INTEL® NM10 Express chipset
■ Memory	■ 2 * DDR3 800/1067MHz Single CH up to 4GB
■ Expansion Slots	■ 1 * PCI slot ■ 1 * Mini PCI-E socket
■ Storage	■ 2 * Serial ATAI 3Gb/s + 2 * Serial ATAIII 6Gb/s connectors
■ Audio	■ Integrated Realtek ALC662 HD Audio CODEC with 6-CH
■ Ethernet LAN	■ 2 * Realtek RTL8111EVL PCI-E Gigabit Ethernet LAN
■ USB	■ Embedded 8 * USB 2.0/1.1
■ Special Features	■ Support ACPI S3 ■ Support CPU Smart FAN & DC FAN
■ LVDS	■ Onboard 24-bits Dual Channel LVDS connector
■ Rear Panel I / O	■ 4 * USB 2.0/1.1 ports ■ 1 * PS/2 KB/MS connector ■ 2 * RJ-45 port ■ 1 * Audio port (Line-in, MIC and Line-out) ■ 1 * VGA port ■ 1 * HDMI port ■ 1 * COM port
■ Internal I / O	■ 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports ■ CPU / Chassis Fan connectors ■ 1 * 24-pin ATX Power connector ■ 1 * COM header (for RS-232/422/485) ■ 1 * chassis intrusion header ■ 1 * 2-pin SPDIF out header ■ 1 * Parallel header ■ 1 * GPIO header
■ BIOS	■ AMI 16MB DIP-SPI Flash ROM
■ Form Factor	■ Mini ITX Form Factor(170mmx170mm)